



NTN-SNR BEARING RULMENTI S.R.L.



skf FSAF 1617 T SAF and SAW pillow blocks
with bearings on an adapter sleeve

Bearing No. FSAF 1617 T

FSAF 1617 T Bearing 2D drawings and 3D CAD models

d_a	74.612 mm
D_a	180 mm
C_a	69.799 mm
A_1	111.125 mm
A_2	231.775 mm
b_a	52.388 mm
H	222.25 mm
H_1	114.3 mm
H_2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J_1	60.325 mm
L	387.35 mm
N_1	22.225 mm
R_1	66.675 mm
R_2	30.163 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	47.625 mm
Housing	FSAF 617
Bearing	1317 K
Adapter sleeve assembly	SNW 117x2.15/16
Stabilizing ring	2 x SR-1617
Taconite seal	TER 184
End plug (suffix Y)	EPR 10



NTN-SNR BEARING RULMENTI S.R.L.

Max. speed for Taconite seal	1050 r/min
P _{60°}	104 kN
P _{90°}	62.3 kN
P _{120°}	39.1 kN
P _{150°}	35.6 kN
P _{180°}	42.9 kN
P _a	10.5 kN
Mass pillow block	25.5 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	365.71 g