




NTN-SNR BEARING RULMENTI S.R.L.



skf SAFS 22534 x 6 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 22534 x 6 TLC

SAFS 22534 x 6 TLC Bearing 2D drawings and 3D CAD models

d_a	152.4 mm
D_a	309.999 mm
C_a	95.809 mm
A_1	171.45 mm
A_2	247.65 mm
S	4.763 mm
b_a	74.612 mm
H	360.363 mm
H_1	179.4 mm
H_2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J_1	107.95 mm
L	628.65 mm
N_1	28.575 mm
R_1	115.888 mm
R_2	37.306 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	54.769 mm
Housing	SAFS 534
Bearing	22234 CCK/W33
Adapter sleeve assembly	SNW 34x6
Stabilizing ring	SR-34-0
Labyrinth ring	2 x LOR 141



NTN-SNR BEARING RULMENTI S.R.L.

PosiTrac Plus contact element	2 x B10724-140
End plug (suffix Y)	EPR 18
Max. speed for PosiTrac Plus seal	950 r/min
P _{60°}	345 kN
P _{90°}	207 kN
P _{120°}	127 kN
P _{150°}	113 kN
P _{180°}	133 kN
P _a	43.6 kN
Mass pillow block	165 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g