




NTN-SNR BEARING RULMENTI S.R.L.



skf SAF 22617 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22617 TLC

SAF 22617 TLC Bearing 2D drawings and 3D CAD models

d_a	74.612 mm
D_a	180 mm
C_a	69.799 mm
A_1	111.125 mm
A_2	173.037 mm
S	4.763 mm
b_a	48.419 mm
H	222.25 mm
H_1	114.3 mm
H_2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
L	387.35 mm
N_1	25.4 mm
R_1	66.675 mm
R_2	30.163 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	44.45 mm
Housing	SAF 617
Stabilizing ring	SR-20-17
Labyrinth ring	2 x LOR 184
PosiTrac Plus contact element	2 x B10724-184
End plug (suffix Y)	EPR 10
Max. speed for PosiTrac	1950 r/min



NTN-SNR BEARING RULMENTI S.R.L.

Plus seal	
P _{60°}	94.3 kN
P _{90°}	56.5 kN
P _{120°}	35.6 kN
P _{150°}	32 kN
P _{180°}	38.3 kN
P _a	15.3 kN
Mass pillow block	33.9 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g