



# NTN-SNR BEARING RULMENTI S.R.L.



skf SSAFS 22517 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22517 T

SSAFS 22517 T Bearing 2D drawings and 3D CAD models

$d_a$	74.612 mm
$D_a$	150 mm
$C_a$	45.796 mm
$A_1$	88.9 mm
$A_2$	195.275 mm
S	4.763 mm
$b_a$	35.719 mm
H	187.325 mm
$H_1$	95.25 mm
$H_2$	38.1 mm
L	330.2 mm
$R_1$	53.975 mm
$R_2$	22.225 mm
$R_G$	3/8 NPT
$P_G$	1/8 NPT
h	34.925 mm
Housing	SSAFS 517
Bearing	22217 EK
Adapter sleeve assembly	SNW 17x2.15/16
Stabilizing ring	SR-17-14
Taconite seal	TER 53
End plug (suffix Y)	EPR 9
Max. speed for Taconite seal	1050 r/min
$P_{60^\circ}$	78.7 kN
$P_{90^\circ}$	47.2 kN



## NTN-SNR BEARING RULMENTI S.R.L.

$P_{120^\circ}$	28.9 kN
$P_{150^\circ}$	26.7 kN
$P_{180^\circ}$	32 kN
$P_a$	9.25 kN
Mass pillow block	24.9 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Initial grease fill	110.56 g