




NTN-SNR BEARING RULMENTI S.R.L.



skf SAF 1611 x 2 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1611 x 2

SAF 1611 x 2 Bearing 2D drawings and 3D CAD models

d_a	50.8 mm
D_a	120 mm
C_a	52.807 mm
A_1	79.375 mm
A_2	123.825 mm
b_a	29.369 mm
H	157.162 mm
H_1	82.55 mm
H_2	30.163 mm
J min.	206.375 mm
J max.	241.3 mm
L	279.4 mm
N_1	19.05 mm
R_1	44.45 mm
R_2	25.4 mm
R_G	1/4 NPT
P_G	1/8 NPT
h	38.1 mm
Housing	SAF 611
Stabilizing ring	2 x SR-1611
Labyrinth ring	2 x LER 25
End plug (suffix Y)	EPR 5
Bearing limiting speed	7500 r/min
P_{60°	43.1 kN
P_{90°	25.8 kN



NTN-SNR BEARING RULMENTI S.R.L.

P_{120°	16 kN
P_{150°	14.7 kN
P_{180°	17.8 kN
P_a	4.8 kN
Mass pillow block	12.4 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	136.08 g