



NTN-SNR BEARING RULMENTI S.R.L.



1.938 Inch | 49.225 Millimeter x 4.875 Inch |
 123.83 Millimeter x 3.25 Inch | 82.55 Millimeter skf
 FSAF 22611 SAF and SAW pillow blocks with
 bearings on an adapter sleeve

Bearing No. FSAF 22611

FSAF 22611 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	14.103
EAN	7316576663505
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Tapered Adapter Sleeve
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22311 EK
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch - Metric	Inch
Other Features	Double Row Heavy Duty
Long Description	4 Bolt Pillow Block; 1-15/16" Bore; 3-1/4" Base to Center Height; Tapered Adapter Sleeve Mount; Spherical Roller Bearing;



NTN-SNR BEARING RULMENTI S.R.L.

	8-1/8" Minimum Bolt Spacing; 9-1/2" Bolt Spacing Maximum;
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	FSAF 22611
Weight / LBS	29
B	3.25 Inch 82.55 Millimeter
Bolt Spacing Minimum	8.125 Inch 206.375 Millimeter
d	1.938 Inch 49.225 Millimeter
Nominal Bolt Center to Center	8.8 Inch 223 Millimeter
D	4.875 Inch 123.83 Millimeter
Actual Bolt Center to Center	0 Inch 0 Millimeter
Bolt Spacing Maximum	9.5 Inch 241.3 Millimeter
mounting:	Four-Bolt Base
series:	FSAF
housing material:	Cast Iron
d _a	49.212 mm
D _a	120 mm
C _a	52.807 mm
A ₁	79.375 mm
A ₂	123.825 mm
S	4.763 mm
b _a	36.513 mm
H	157.162 mm



NTN-SNR BEARING RULMENTI S.R.L.

H ₁	82.55 mm
H ₂	30.163 mm
J min.	206.375 mm
J max.	241.3 mm
J ₁	50.8 mm
L	279.4 mm
N ₁	15.875 mm
R ₁	44.45 mm
R ₂	25.4 mm
R _G	1/4 NPT
P _G	1/8 NPT
h	36.513 mm
Housing	FSAF 611
Stabilizing ring	SR-13-11
Labyrinth ring	2 x LER 24
End plug (suffix Y)	EPR 5
Bearing limiting speed	5600 r/min
P _{60°}	35.6 kN
P _{90°}	21.4 kN
P _{120°}	13.3 kN
P _{150°}	12 kN
P _{180°}	14.2 kN
P _a	6.94 kN
Mass pillow block	14.1 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.5 in
Initial grease fill	68.04 g