



NTN-SNR BEARING RULMENTI S.R.L.



skf SAW 23534 x 5.7/8 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAW 23534 x 5.7/8 TLC

SAW 23534 x 5.7/8 TLC Bearing 2D drawings and 3D CAD models

d_a	149.225 mm
D_a	309.999 mm
C_a	119.812 mm
A_1	171.45 mm
A_2	242.887 mm
S	4.763 mm
b_a	86.519 mm
H	360.363 mm
H_1	179.375 mm
H_2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J_1	107.95 mm
L	628.65 mm
N_1	28.575 mm
R_1	115.888 mm
R_2	37.306 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	54.769 mm
Housing	SAW 534
Bearing	23234 CCK/W33
Adapter sleeve assembly	SNW 134x5.7/8
Stabilizing ring	SR-34-0
Labyrinth ring	2 x LOR 139



NTN-SNR BEARING RULMENTI S.R.L.

PosiTrac Plus contact element	2 x B10724-130
End plug (suffix Y)	EPR 18
Max. speed for PosiTrac Plus seal	950 r/min
P_{60°	234 kN
P_{90°	140 kN
P_{120°	85.9 kN
P_{150°	77 kN
P_{180°	92.5 kN
P_a	56 kN
Mass pillow block	132 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g