




NTN-SNR BEARING RULMENTI S.R.L.



skf FSAF 22616 SAF and SAW pillow blocks
with bearings on an adapter sleeve

Bearing No. FSAF 22616

FSAF 22616 Bearing 2D drawings and 3D CAD models

d_a	68.263 mm
D_a	170 mm
C_a	67.793 mm
A_1	98.425 mm
A_2	160.338 mm
S	4.763 mm
b_a	46.038 mm
H	209.55 mm
H_1	107.95 mm
H_2	44.45 mm
J min.	269.875 mm
J max.	320.675 mm
J_1	53.975 mm
L	361.95 mm
N_1	19.05 mm
R_1	63.5 mm
R_2	26.988 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	42.862 mm
Housing	FSAF 616
Bearing	22316 EK
Adapter sleeve assembly	SNW 116x2.11/16
Stabilizing ring	SR-19-16
Labyrinth ring	2 x LOR 44



NTN-SNR BEARING RULMENTI S.R.L.

End plug (suffix Y)	EPR 8
Bearing limiting speed	4000 r/min
P _{60°}	92.5 kN
P _{90°}	55.6 kN
P _{120°}	33.8 kN
P _{150°}	30.7 kN
P _{180°}	36.9 kN
P _a	14 kN
Mass pillow block	32.2 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	181.44 g