




NTN-SNR BEARING RULMENTI S.R.L.



skf SAF 22632 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22632 TLC

SAF 22632 TLC Bearing 2D drawings and 3D CAD models

d_a	138.113 mm
D_a	339.999 mm
C_a	123.8 mm
A_1	190.5 mm
A_2	273.05 mm
S	4.763 mm
b_a	87.313 mm
H	401.637 mm
H_1	200.025 mm
H_2	79.375 mm
J min.	549.275 mm
J max.	619.125 mm
J_1	114.3 mm
L	711.2 mm
N_1	34.925 mm
R_1	120.65 mm
R_2	42.069 mm
R_G	1 NPT
P_G	1/4 NPT
h	68.263 mm
Housing	SAF 632
Bearing	22332 CCK/W33
Adapter sleeve assembly	SNW 132x5.7/16
Stabilizing ring	SR-38-32
Labyrinth ring	2 x LOR 130



NTN-SNR BEARING RULMENTI S.R.L.

PosiTrac Plus contact element	2 x B10724-130
End plug (suffix Y)	EPR 16
Max. speed for PosiTrac Plus seal	1050 r/min
P_{60°	290 kN
P_{90°	173 kN
P_{120°	107 kN
P_{150°	94.3 kN
P_{180°	113 kN
P_a	54.3 kN
Mass pillow block	178 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	1672.65 g