



NTN-SNR BEARING RULMENTI S.R.L.



skf SAFS 22517 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 22517 T

SAFS 22517 T Bearing 2D drawings and 3D CAD models

d_a	74.612 mm
D_a	150 mm
C_a	45.796 mm
A_1	88.9 mm
A_2	195.262 mm
S	4.763 mm
b_a	35.719 mm
H	187.325 mm
H_1	95.25 mm
H_2	38.1 mm
J min.	250.825 mm
J max.	279.4 mm
L	330.2 mm
N_1	23.813 mm
R_1	53.975 mm
R_2	22.225 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	34.925 mm
Housing	SAFS 517
Stabilizing ring	SR-17-14
Taconite seal	TER 53
End plug (suffix Y)	EPR 9
Max. speed for Taconite seal	1050 r/min
P_{60°	78.7 kN



NTN-SNR BEARING RULMENTI S.R.L.

P _{90°}	47.2 kN
P _{120°}	28.9 kN
P _{150°}	26.7 kN
P _{180°}	32 kN
P _a	9.25 kN
Mass pillow block	24.5 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	110.56 g