




NTN-SNR BEARING RULMENTI S.R.L.



skf FSAF 22520 x 3.3/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 22520 x 3.3/8 T

FSAF 22520 x 3.3/8 T Bearing 2D drawings and 3D CAD models

d_a	85.725 mm
D_a	180 mm
C_a	55.804 mm
A_1	111.125 mm
A_2	222.25 mm
S	4.763 mm
b_a	44.45 mm
H	217.488 mm
H_1	114.3 mm
H_2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J_1	60.325 mm
L	387.35 mm
N_1	22.225 mm
R_1	58.737 mm
R_2	30.163 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	42.069 mm
Housing	FSAF 520
Stabilizing ring	SR-20-17
Taconite seal	TER 101
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	900 r/min



NTN-SNR BEARING RULMENTI S.R.L.

P _{60°}	119 kN
P _{90°}	71.2 kN
P _{120°}	44.5 kN
P _{150°}	40 kN
P _{180°}	48.9 kN
P _a	13.8 kN
Mass pillow block	28.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g