



# NTN-SNR BEARING RULMENTI S.R.L.



skf SAF 23056 KATLC x 9.15/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 23056 KATLC x 9.15/16

SAF 23056 KATLC x 9.15/16 Bearing 2D drawings and 3D CAD models

$d_a$	252.412 mm
$D_a$	419.999 mm
$C_a$	147.803 mm
$A_1$	228.6 mm
$A_2$	315.119 mm
$b_a$	100.806 mm
H	495.3 mm
$H_1$	250.825 mm
$H_2$	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
$J_1$	139.7 mm
L	869.95 mm
$N_1$	41.275 mm
$R_1$	163.512 mm
$R_2$	50.8 mm
$R_G$	1 NPT
$P_G$	1/4 NPT
h	73.025 mm
Housing	SAF 056 KAUB
Bearing	23056 CCK/W33
Adapter sleeve assembly	SNP 3056x9.15/16
Stabilizing ring	2 x A8819
Labyrinth ring	2 x LOR 607
PosiTrac Plus contact element	2 x B10724-607



## NTN-SNR BEARING RULMENTI S.R.L.

End plug (suffix Y)	X-5217-2
Max. speed for PosiTrac Plus seal	575 r/min
P <sub>60°</sub>	449 kN
P <sub>90°</sub>	271 kN
P <sub>120°</sub>	169 kN
P <sub>150°</sub>	151 kN
P <sub>180°</sub>	185 kN
P <sub>a</sub>	89 kN
Mass pillow block	316 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	1017 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g