



# NTN-SNR BEARING RULMENTI S.R.L.



skf FSAF 22617 x 2.13/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 22617 x 2.13/16

FSAF 22617 x 2.13/16 Bearing 2D drawings and 3D CAD models

$d_a$	71.438 mm
$D_a$	180 mm
$C_a$	69.799 mm
$A_1$	111.125 mm
$A_2$	173.037 mm
S	4.763 mm
$b_a$	48.419 mm
H	222.25 mm
$H_1$	114.3 mm
$H_2$	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
$J_1$	60.325 mm
L	387.35 mm
$N_1$	22.225 mm
$R_1$	65.088 mm
$R_2$	30.163 mm
$R_G$	3/8 NPT
$P_G$	1/8 NPT
h	44.45 mm
Housing	FSAF 617
Bearing	22317 EK
Adapter sleeve assembly	SNW 117x2.13/16
Stabilizing ring	SR-20-17
Labyrinth ring	2 x LOR 182



## NTN-SNR BEARING RULMENTI S.R.L.

End plug (suffix Y)	EPR 10
Bearing limiting speed	3800 r/min
$P_{60^\circ}$	104 kN
$P_{90^\circ}$	62.3 kN
$P_{120^\circ}$	39.1 kN
$P_{150^\circ}$	35.6 kN
$P_{180^\circ}$	42.7 kN
$P_a$	15.3 kN
Mass pillow block	34 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g