




NTN-SNR BEARING RULMENTI S.R.L.



skf SSAFS 22515 x 2.1/2 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22515 x 2.1/2 T

SSAFS 22515 x 2.1/2 T Bearing 2D drawings and 3D CAD models

d_a	63.5 mm
D_a	130 mm
C_a	37.008 mm
A_1	79.375 mm
A_2	195.275 mm
S	3.175 mm
b_a	32.544 mm
H	161.925 mm
H_1	82.55 mm
H_2	30.163 mm
L	285.75 mm
R_1	46.038 mm
R_2	21.431 mm
R_G	1/4 NPT
P_G	1/8 NPT
h	28.575 mm
Housing	SSAFS 515
Bearing	22215 EK
Adapter sleeve assembly	SNW 15x2.1/2
Stabilizing ring	SR-15-0
Taconite seal	TER 38
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1250 r/min
P_{60°	104 kN
P_{90°	59.6 kN



NTN-SNR BEARING RULMENTI S.R.L.

P_{120°	36.9 kN
P_{150°	33.4 kN
P_{180°	40 kN
P_a	6.94 kN
Mass pillow block	14.3 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	8
Initial grease fill	68.04 g