




# NTN-SNR BEARING RULMENTI S.R.L.



skf SSAFS 23056 KAT x 9.15/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 23056 KAT x 9.15/16

SSAFS 23056 KAT x 9.15/16 Bearing 2D drawings and 3D CAD models

$d_a$	252.412 mm
$D_a$	419.999 mm
$C_a$	147.803 mm
$A_1$	228.6 mm
$A_2$	379.425 mm
$b_a$	100.806 mm
$H$	495.3 mm
$H_1$	250.825 mm
$H_2$	101.6 mm
$L$	869.95 mm
$R_1$	163.512 mm
$R_2$	50.8 mm
$R_G$	1 NPT
$P_G$	1/4 NPT
$h$	73.025 mm
Housing	SSAFS 056 KAUB
Bearing	23056 CCK/W33
Stabilizing ring	2 x A8819
Taconite seal	2 x TER 607
End plug (suffix Y)	X-5217-2
Max. speed for Taconite seal	310 r/min
$P_{60^\circ}$	669 kN
$P_{90^\circ}$	400 kN
$P_{120^\circ}$	249 kN
$P_{150^\circ}$	222 kN



## NTN-SNR BEARING RULMENTI S.R.L.

$P_{180^\circ}$	267 kN
$P_a$	89 kN
Mass pillow block	316 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Initial grease fill	3515.4 g