



NTN-SNR BEARING RULMENTI S.R.L.



skf SAFS 23052 KATLC x 9.7/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 23052 KATLC x 9.7/16

SAFS 23052 KATLC x 9.7/16 Bearing 2D drawings and 3D CAD models

d_a	239.713 mm
D_a	399.999 mm
C_a	117.805 mm
A_1	222.25 mm
A_2	311.15 mm
b_a	96.838 mm
H	473.075 mm
H_1	241.3 mm
H_2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J_1	133.35 mm
L	831.85 mm
N_1	41.275 mm
R_1	130.175 mm
R_2	46.831 mm
R_G	1 NPT
P_G	1/4 NPT
h	69.85 mm
Housing	SAFS 052 KA
Bearing	23052 CCK/W33
Adapter sleeve assembly	SNP 3052x9.7/16
Stabilizing ring	2 x A8898
Labyrinth ring	2 x LOR 553
PosiTrac Plus contact element	2 x B10724-178



NTN-SNR BEARING RULMENTI S.R.L.

End plug (suffix Y)	X-5217-2
Max. speed for PosiTrac Plus seal	600 r/min
P _{60°}	691 kN
P _{90°}	414 kN
P _{120°}	260 kN
P _{150°}	236 kN
P _{180°}	285 kN
P _a	81.4 kN
Mass pillow block	342 kg
Cap bolt	1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g