




# NTN-SNR BEARING RULMENTI S.R.L.



skf SAF 1622 x 4 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1622 x 4 TLC

SAF 1622 x 4 TLC Bearing 2D drawings and 3D CAD models

$d_a$	101.6 mm
$D_a$	240 mm
$C_a$	89.789 mm
$A_1$	133.35 mm
$A_2$	206.375 mm
$b_a$	48.419 mm
H	287.337 mm
$H_1$	152.4 mm
$H_2$	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
$J_1$	82.55 mm
L	466.725 mm
$N_1$	25.4 mm
$R_1$	79.375 mm
$R_2$	36.513 mm
$R_G$	1/2 NPT
$P_G$	1/4 NPT
h	63.5 mm
Housing	SAF 622
Stabilizing ring	2 x SR-1622
Labyrinth ring	2 x LOR 110
PosiTrac Plus contact element	2 x B10724-109
End plug (suffix Y)	EPR 13
Max. speed for PosiTrac	1450 r/min



## NTN-SNR BEARING RULMENTI S.R.L.

Plus seal	
P <sub>60°</sub>	189 kN
P <sub>90°</sub>	113 kN
P <sub>120°</sub>	73.8 kN
P <sub>150°</sub>	68.1 kN
P <sub>180°</sub>	84.5 kN
P <sub>a</sub>	16.7 kN
Mass pillow block	62.8 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	765.45 g