



NTN-SNR BEARING RULMENTI S.R.L.



skf SAF 22622 x 3.13/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22622 x 3.13/16

SAF 22622 x 3.13/16 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------|-----------------|
| d_a | 96.838 mm |
| D_a | 240 mm |
| C_a | 89.789 mm |
| A_1 | 133.35 mm |
| A_2 | 206.375 mm |
| S | 4.763 mm |
| b_a | 63.5 mm |
| H | 287.337 mm |
| H_1 | 152.4 mm |
| H_2 | 60.325 mm |
| J min. | 371.475 mm |
| J max. | 406.4 mm |
| J_1 | 82.55 mm |
| L | 466.725 mm |
| N_1 | 25.4 mm |
| R_1 | 79.375 mm |
| R_2 | 36.513 mm |
| R_G | 1/2 NPT |
| P_G | 1/4 NPT |
| h | 61.119 mm |
| Housing | SAF 622 |
| Bearing | 22322 EK |
| Adapter sleeve assembly | SNW 122x3.13/16 |
| Stabilizing ring | SR-0-22 |
| Labyrinth ring | 2 x LOR 107 |
| | |



NTN-SNR BEARING RULMENTI S.R.L.

| | |
|--|-------------|
| End plug (suffix Y) | EPR 13 |
| Bearing limiting speed | 2800 r/min |
| P _{60°} | 189 kN |
| P _{90°} | 113 kN |
| P _{120°} | 73.8 kN |
| P _{150°} | 68.1 kN |
| P _{180°} | 84.5 kN |
| P _a | 26.7 kN |
| Mass pillow block | 69.3 kg |
| Cap bolt | 2 x 1-8 UNC |
| Cap bolt recommended tightening torque | 1220 N · m |
| Cap bolt, SAE grade | 8 |
| Appropriate attachment bolt size G | 0.875 in |
| Initial grease fill | 382.73 g |