



NTN-SNR BEARING RULMENTI S.R.L.



7212 BEGAM Bearing 2D drawings and 3D CAD models

60 mm x 110 mm x 22 mm skf 7212 BEGAM
Single row angular contact ball bearings

Bearing No. 7212 BEGAM

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.82
EAN	7316577648945
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Preload	Light
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Width; Open; Yes Flush Ground; Ball Bearing; Single



NTN-SNR BEARING RULMENTI S.R.L.

	Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7212 BEGAM
Weight / LBS	1.808
D	4.331 Inch 110 Millimeter
B	0.866 Inch 22 Millimeter
d	2.362 Inch 60 Millimeter
bore diameter:	60 mm
radial static load capacity:	50 kN
outside diameter:	110 mm
cage material:	Brass
overall width:	22 mm
outer ring width:	22 mm
contact angle:	40 °
maximum rpm:	7500 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1.5 mm
radial dynamic load capacity:	61 kN
series:	72
d	60 mm



NTN-SNR BEARING RULMENTI S.R.L.

D	110 mm
B	22 mm
d ₁	79.6 mm
d ₂	69.32 mm
D ₁	91.55 mm
a	47 mm
r _{1,2} min.	1.5 mm
r _{3,4} min.	1 mm
d _a min.	69 mm
D _a max.	101 mm
D _b max.	104 mm
r _a max.	1.5 mm
r _b max.	1 mm
Basic dynamic load rating C	61 kN
Basic static load rating C ₀	50 kN
Fatigue load limit P _u	2.12 kN
Reference speed	7000 r/min
Limiting speed	9500 r/min
Calculation factor A	0.0344
Calculation factor k _r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y ₀	0.26
Calculation factor Y ₂	0.57
Calculation factor X	0.57
Calculation factor Y ₀	0.52
Calculation factor Y ₁	0.55
Calculation factor Y ₂	0.93
Mass bearing	0.8 kg