



NTN-SNR BEARING RULMENTI S.R.L.

55 mm x 100 mm x 25 mm NTN N2211C4
Single row cylindrical roller bearings

Bearing No. N2211C4

d	55 mm
D	100 mm
B	25 mm
E	88.5 mm
F	66.5 mm
d1	70.8 mm
rs min	1.5 mm
r1s min	1.1 mm
Radial clearance class	C4
Mass (without HJ ring)	0.76 kg
Dynamic load, C	75.5 kN
Static load, C0	87 kN
Fatigue limit load, Cu	10.6 kN
Nlim (oil)	7,400 rpm
Nlim (grease)	6,300 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.9 Hz
Characteristic outer ring frequency, BPF0	6.44 Hz
Characteristic inner ring frequency, BPF1	8.56 Hz

N2211C4 Bearing 2D drawings and 3D CAD models



NTN-SNR BEARING RULMENTI S.R.L.

da min	63 mm
Da max	93.5 mm
Db min	90 mm
Dc max	87 mm
ra max	1.5 mm
r1a max	1 mm