



NTN-SNR BEARING RULMENTI S.R.L.

12 mm x 28 mm x 8 mm NTN 6001ZZC3/5C
Single row deep groove ball bearings

Bearing No. 6001ZZC3/5C

d	12 mm
D	28 mm
B	8 mm
rs min	0.3 mm
Radial clearance class	C3
Mass	0.02 kg
Dynamic load, C	5.1 kN
Static load, C0	2.39 kN
Fatigue limit load, Cu	0.11 kN
f0	13.2
Nlim (grease)	26,000 rpm
Min operating temperature, Tmin	-30 ° C
Max operating temperature, Tmax	175 ° C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BPF1	4.93 Hz
da min	14 mm
Da max	26 mm
ra max	0.3 mm
Category	Single Row Ball Bearings

6001ZZC3/5C Bearing 2D drawings and 3D CAD models



NTN-SNR BEARING RULMENTI S.R.L.

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0692314598382
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	12MM Bore; 28MM Outside Diameter; 8MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C3-Loose Internal Clearance; Steel
Other Features	Deep Groove Chevron SRI2 Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.0546
Bore	0.472 Inch 12 Millimeter



NTN-SNR BEARING RULMENTI S.R.L.

Outer Race Width	0.315 Inch 8 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	1.102 Inch 28 Millimeter