




NTN-SNR BEARING RULMENTI S.R.L.



7201BG Bearing 2D drawings and 3D CAD models

12,000 mm x 32,000 mm x 10,000 mm NTN 7201BG Single row or matched pairs of angular contact ball bearings

Bearing No. 7201BG

Size	12x32x10 mm
Bore Diameter	12,000 mm
Outer Diameter	32,000 mm
Width	10,000 mm
d	12,000 mm
D	32,000 mm
B	10,000 mm
C	10,000 mm
a	14 mm
Contact angle	40 °
rs min	0.6 mm
r1s min	0.3 mm
Radial clearance class	CN
Mass	0.04 kg
Dynamic load, C	7 kN
Static load, C0	3.65 kN
Fatigue limit load, Cu	0.17 kN
Nlim (oil)	28,000 rpm
Nlim (grease)	21,000 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
da min	16.5 mm
db min	14.5 mm



NTN-SNR BEARING RULMENTI S.R.L.

Da max	27.5 mm
Db max	29.5 mm
r1a max	0.3 mm
ra max	0.3 mm
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.037
EAN	4547359436426
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	12MM Bore; 32MM Outside Diameter; 10MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing



NTN-SNR BEARING RULMENTI S.R.L.

UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	7201BG
Outside Diameter	1.26 Inch 32 Millimeter
Width	0.394 Inch 10 Millimeter
Bore	0.472 Inch 12 Millimeter
bore diameter:	12 mm
radial static load capacity:	3650 N
outside diameter:	32 mm
operating temperature range:	-40 to 120 ° C
overall width:	10 mm
cage material:	Steel
contact angle:	40 °
outer ring width:	10 mm
row type & fill slot:	Single-Row Non-Fill Slot
maximum rpm:	28000 rpm
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 0
closure type:	Open
fillet radius:	0.6 mm
snap ring included:	Without Snap Ring
series:	72B
bearing material:	High Carbon Chrome Steel
weight:	0.035 kg
radial dynamic load capacity:	7000 N



NTN-SNR BEARING RULMENTI S.R.L.

manufacturer product page:

[Click here](#)