



NTN-SNR BEARING RULMENTI S.R.L.

75 mm x 160 mm x 37 mm NTN 7315BL1G
Single row or matched pairs of angular contact ball bearings

Bearing No. 7315BL1G

d	75 mm
D	160 mm
B	37 mm
a	68 mm
Contact angle	40 °
rs min	2.1 mm
r1s min	1.1 mm
Radial clearance class	CN
Mass	3.51 kg
Dynamic load, C	118 kN
Static load, C0	89.3 kN
Fatigue limit load, Cu	3.75 kN
Nlim (oil)	5,400 rpm
Nlim (grease)	4,100 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	4.22 Hz
Characteristic outer ring frequency, BPF0	4.53 Hz
Characteristic inner ring frequency, BPF1	6.47 Hz

7315BL1G Bearing 2D drawings and 3D CAD models



NTN-SNR BEARING RULMENTI S.R.L.

da min	87 mm
db min	82 mm
Da max	148 mm
Db max	153 mm
r1a max	1 mm
ra max	2 mm
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	3.52
EAN	4547359452327
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	75MM Bore; 160MM Outside Diameter; 37MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring



NTN-SNR BEARING RULMENTI S.R.L.

Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	7315BL1G
Weight / LBS	7.757
Width	1.457 Inch 37 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
Bore	2.953 Inch 75 Millimeter
bore diameter:	75 mm
radial static load capacity:	97500 N
outside diameter:	160 mm
operating temperature range:	-40 to 120 ° C
overall width:	37 mm
cage material:	Steel
contact angle:	40 °
outer ring width:	37 mm
row type & fill slot:	Single-Row Non-Fill Slot
maximum rpm:	5400 rpm
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 0
closure type:	Open
fillet radius:	2.1 mm
snap ring included:	Without Snap Ring
series:	73B
bearing material:	High Carbon Chrome Steel



NTN-SNR BEARING RULMENTI S.R.L.

weight:	3.510 kg
radial dynamic load capacity:	125000 N
manufacturer product page:	Click here